



Specification Data Sheet | Model: H440A-EU(W)



ABBI HIGHWAY 2000 Ltr

The Highway Tow ABBI consists of a steel in steel U.N. (United Nations) approved IBC (Intermediate Bulk Container) suitable for transporting diesel fuel on the highway. The ABBI is fully bunded to ensure compliance with Environmental Regulations for fuel storage PPG2 (Pollution Prevention Guidelines).

- 🔸 Secure lockable access hatch to enclose pumping equipment.
- 🔸 110% bund capacity.
- 🔸 Direct access into the inner tank via the manhole for cleaning and inspection.
- 🔸 Full load lifting can be achieved using 4 lifting eyes.
- 🔸 Can be operated from ground level when placed on truck beds.
- 🔸 Internal baffles for safe towing.
- 🔸 Tank easily demountable from trailer.
- 🔸 Type approval number: e11/2007*46*0770*00.

SPECIFICATION

Standard Tank Fittings: 3" Fill Cap : 1" Pump Draw Off : Contents Gauge : Pressure / Vacuum Vent : Breather Vent : 2 x ½" Generator Feed & Return Ports : Pump Mounting Bracket : Inspection Manhole

Capacity (Brim Full) Litres:	2000	Brake Specification:	200 x 50 auto reverse brakes
Capacity (Brim Full) Gallons:	440	Chassis:	5mm hot dipped galvanised
Dimensions Length (mm):	3520	Wheels & Tyres:	4 off 185R14 6ply
Dimensions Width (mm):	1657	Mudguards:	Moulded polythene
Dimensions Height (mm):	1882	Lighting:	Full EU 13 pin plug. Wired to ISO standard with fog & reverse lamps
Cabinet Dimensions (mm) Opening Size: W835 x H500 x D400		Coupling Specification:	Knott KFG 30. Ball or Eye as specified
Weight Unladen (kg):	1115	Jockey Wheel:	48mm adjustable, telescopic serrated
Weight Laden (kg):	2950*	Rear Dropleg:	1 x fitted
Bund Material (thickness):	S235 (3mm)	Design Approvals:	ADR IBC Type 31A
Inner Tank Material (thickness):	S235 (3mm)	Design Standards:	Bunded to COP Regulations (PPG2)
Suspension:	2 close coupled rubber suspension axles		

Notes

* Specific gravity of diesel taken as 0.9 for this calculation. Both axles together have a gross rating of 3000kg.